

Mass-Storage Systems

Fan Wu

Department of Computer Science and Engineering
Shanghai Jiao Tong University
Spring 2020



The First Commercial Disk Drive



1956
IBM RAMDAC computer
included the IBM Model
350 disk storage system

5M (7 bit) characters
50 x 24 inch platters
Access time = < 1 second



Magnetic Tape

- Was early secondary-storage medium
 - Evolved from open spools to cartridges
- Relatively permanent and holds large quantities of data
- Access time slow
- Random access ~1000 times slower than disk
- Mainly used for backup, storage of infrequently-used data, transfer medium between systems
- Kept in spool and wound or rewound past read-write head
- Once data under head, transfer rates comparable to disk
 - 140MB/sec and greater
- 200GB to 1.5TB typical storage
- Common technologies are LTO-{3,4,5} and T10000



Modern Disk Drive




3.5 inch SATA HDD



Different Sized Disk Drives



Read-Write Arm and Head



Head stack



Read-write head



Solid-State Drive (SSD)

SSDs use microchips which retain data in non-volatile memory chips and contain no moving parts




Operating Systems

7



Moving-head Disk Mechanism




Operating Systems

8



Disk Structure




0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
---	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	-------

Operating Systems

11



Disk Structure



Operating Systems

12



Overview of Mass Storage Structure

- **Magnetic disks** provide bulk of secondary storage of modern computers
 - Drives rotate at 60 to 250 times per second
 - **Transfer rate** is rate at which data flows between drive and computer
 - **Positioning time (random-access time)** is time to move disk arm to desired cylinder (**seek time**) and time for desired sector to rotate under the disk head (**rotational latency**)

Operating Systems

14



Disk Scheduling

- There are many sources of disk I/O request
 - OS, System processes, Users processes
- OS maintains queue of requests, per disk or device
- Idle disk can immediately work on I/O request, busy disk means work must be queued
 - Optimization algorithms only make sense when a queue exists
- The operating system is responsible for using hardware efficiently — for the disk drives, this means having a fast access time and disk bandwidth
 - **Minimize seek time** \approx seek distance
 - What about rotational latency?
 - › Difficult for OS to calculate
- Several algorithms exist to schedule the servicing of disk I/O requests
- We illustrate scheduling algorithms with a request queue (0-199)

98, 183, 37, 122, 14, 124, 65, 67	Head pointer 53
-----------------------------------	-----------------

Operating Systems

15



Disk-Scheduling Algorithms


- First-Come, First-Served (FCFS) Scheduling
- Shortest Seek Time First (SSTF) Scheduling
- SCAN Scheduling
- C-SCAN Scheduling
- LOOK/C-LOOK Scheduling

Operating Systems

16



FCFS Scheduling




Operating Systems

17



SSTF Scheduling

- Shortest Seek Time First selects the request with the minimum seek time from the current head position




Operating Systems

19



SCAN

- The disk arm starts at one end of the disk, and moves toward the other end, servicing requests until it gets to the other end of the disk, where the head movement is reversed and service continues.




Operating Systems

21



C-SCAN

- The head moves from one end of the disk to the other, servicing requests as it goes. When it reaches the other end, it immediately returns to the beginning of the disk, without servicing any requests on the return trip.




Operating Systems

23



C-LOOK

- Arm only goes as far as the last request in each direction, then reverses direction immediately, without first going all the way to the end of the disk



Operating Systems

25



Pop-Quiz

- Suppose that a disk drive has 5,000 cylinders, numbered 0 to 4999. The drive is currently serving a request at cylinder 143, and the previous request was at cylinder 125. The queue of pending requests, in FIFO order, is:
 - 86, 1470, 913, 1774, 948, 1509, 1022, 1750, 130
- Starting from the current head position, what is the total distance (in cylinders) that the disk arm moves to satisfy all the pending requests for each of the following disk-scheduling algorithms?
 - a) SSTF
 - b) C-LOOK

Homework

- Reading
 - Chapter 11
- Exercise
 - See course website